

Seventec B - 40355

Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.

Product description

- Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.
- Treads 85 mm deep for safe standing.
- Sturdy hinged connection integrated in the treads.
- Optimal stability thanks to the fold-down locking bar on both sides.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Non-slip plastic end caps.

Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Rigid locking bar	Base 1,02 m × 0,45 m	Coating natural	Connection Stile-Rung riveted	Load capacity max. 150 kg
Material Aluminium	Number of treads	Number of treads 2 × 5	Overall base width 0.45 m	Overall length 1.2 m
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth









ZARGES GmbH Zargesstraße 7 Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 www.zarges.com zarges@zarges.de

Effective 12/5/2025



218 mm	EN 131 professional	87 mm	1.200 mm × 460 mm × approx. 230 mm	85 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
serrated	1.1 m	10 years	7.5 kg	2.65 m