

Seventec B - 40355

Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.

Product description

- Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.
- Treads 85 mm deep for safe standing.
- Sturdy hinged connection integrated in the treads.
- Optimal stability thanks to the fold-down locking bar on both sides.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Non-slip plastic end caps.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
Rigid locking bar	1,02 m x 0,45 m	natural	riveted	max. 150 kg
Material	Number of treads	Number of treads	Overall base width	Overall length
Aluminium	5	2 x 5	0.45 m	1.2 m
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth



218 mm	EN 131 professional	87 mm	1.200 mm × 460 mm × approx. 230 mm	85 mm
Type rung/tread serrated	Vertical ladder height 1.1 m	Warranty 10 years	Weight 7.5 kg	Working height 2.65 m
certification-mark-pf TÜV-SÜD				