

## Stationary bridging steps - 40355904

Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides. Large-area platform with guardrail for safe and ergonomic working at heights.

### Product description

- Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides. Large-area platform with guardrail for safe and ergonomic working at heights.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Treads and platform surfaces are made of grooved aluminum (R10) as standard.
- Individually adjustable platform lengths.
- Optionally with chassis for mobile applications.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.



### Hints and special features

We recommend equipping the product in accordance

with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

## Product features

Clear height, stationary	1130 mm
Inclination	60 °
Load capacity	max. 300 kg
Max. load per tread	150 kg
Number of treads	5
Overall span	2203 mm
Platform length	600 mm
Standards	NF EN ISO 14122-4
Tread width	600 mm
Warranty	10 years

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/28/2026

Subject to change or error.