

Stationary bridging steps - 40355957

Stationary or mobile platform for bridging obstacles or as a work platform with access from both sides.
Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Optionally with chassis for mobile applications.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.
- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act

(ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

Product features

Clear height, stationary 1600 mm	Inclination 45 °	Load capacity max. 300 kg	Max. load per tread 150 kg	Number of treads 8
Overall span 4151 mm	Platform length 600 mm	Standards NF EN ISO 14122-4	Tread width 1000 mm	Warranty 10 years