

Seventec B - 40357

Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.

Product description

- Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.
- Treads 85 mm deep for safe standing.
- Sturdy hinged connection integrated in the treads.
- Optimal stability thanks to the fold-down locking bar on both sides.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Non-slip plastic end caps.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
Rigid locking bar	1,34 m x 0,5 m	natural	riveted	max. 150 kg
Material	Number of treads	Number of treads	Overall base width	Overall length
Aluminium	7	2 x 7	0.5 m	1.66 m
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth



ZARGES

218 mm	EN 131 professional	87 mm	1.660 mm × 500 mm × 230 mm	85 mm
Type rung/tread serrated	Vertical ladder height 1.53 m	Warranty 10 years	Weight 10.5 kg	Working height 3.1 m
certification-mark-pf TÜV-SÜD				

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

Subject to change or error.

www.zarges.com

zarges@zarges.de

Effective
2/12/2026

2/2