

Seventec B - 40360

Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.

Product description

- Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.
- Treads 85 mm deep for safe standing.
- Sturdy hinged connection integrated in the treads.
- Optimal stability thanks to the fold-down locking bar on both sides.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Non-slip plastic end caps.







Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Rigid locking bar	Base 1,81 m × 0,56 m	Coating natural	Connection Stile-Rung riveted	Load capacity max. 150 kg
Material Aluminium	Number of treads	Number of treads 2 × 10	Overall base width 0.56 m	Overall length 2.35 m
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth

ZARGES GmbH Zargesstraße 7 Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 www.zarges.com zarges@zarges.de



218 mm	EN 131 professional	87 mm	2.350 mm × 580 mm × 230 mm	85 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
serrated	2.18 m	10 years	15.5 kg	3.75 m