

Seventec L - 40384

The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.

Product description

- The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.
- Smooth external stile surfaces that are comfortable to hold.
- Treads 85 mm deep and with safe, non-slip serrated surfaces.
- Outside width: 400 mm.
- Especially light and easy to carry.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Inside width: 360 mm.



Hints and special features

in accordance with DIN EN 131-1, order No. 40384

includes a stabiliser bar.

Complies with EN 131 Professional.

Product features

Coating	Connection Stile-Rung	Load capacity	Material	Number of treads
---------	-----------------------	---------------	----------	------------------



natural	riveted	max. 150 kg	Aluminium	14
Overall length 3.42 m	Pitch rung/tread 218 mm	Standards EN 131 professional	Stile depth 87 mm	Transport dimensions 3.470 mm × 400 mm × 90 mm
Tread depth 85 mm	Type rung/tread serrated	Warranty 10 years	Weight 11.4 kg	Wide crosspiece 0.8 m
Working height 4.35 m	certification-mark-pf TÜV-SÜD			