

# Roof ladders - 40398

Safe access to various roof pitches via high-stability stationary ladder with rungs arranged eccentrically.

## Product description

- Safe access to various roof pitches via high-stability stationary ladder with rungs arranged eccentrically.
- Safe, square rungs with 2 differently inclined tread surfaces.
- Robust stile sections ensure 80 mm safety clearance between the rungs and the roof surface.
- Problem-free coordination of the ladder to the relevant roof length.
- Off-centre rung arrangement.
- Maximum loading capacity 150 kg.
- Outside width: 340 mm.
- High strength, non-twist rung/stile connections.
- Rungs made from extruded aluminium sections for maximum safety.



## Hints and special features

Connecting straps are included with every roof ladder as standard.

## Product features

Coating	Colour	Connection Stile-Rung	Ladder width	Load capacity
<b>powder-coated</b>	<b>Copper-brown</b>	<b>flanged</b>	<b>340 mm</b>	<b>max. 150 kg</b>
Material	Number of rungs	Overall length	Pitch rung/tread	Stile depth



ZARGES

Aluminium	10	2.8 m	280 mm	110 mm
Transport dimensions 2.800 mm × 340 mm × 110 mm	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years	Weight 4.8 kg