



EFAmix S - 40431

The special ladders for all applications in electrical environments.

Product description

- The special ladders for all applications in electrical environments.
- Can be used for work on electrical installations, thanks to insulating stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61478.
- Aluminium alloy treads, 80 mm deep, with non-slip serrated surface.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in an aluminium storage tray.
- Only 88 mm wide when folded.
- Treads made from extruded aluminium section.



Hints and special features

Complies with EN 131 Professional.

Product features

Base	0,75 m × 0,52 m
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium / plastic



Number of rungs, incl. platform	3
Overall base width	0.52 m
Overall length	1.4 m
Pitch rung/tread	230 mm
Platform height	0.68 m
Platform length	250 mm
Platform width	250 mm
Standards	EN 131 professional
Stile depth	50 mm
Stile depth	50 mm
Stile depth steps/back stay	50mm / 50mm
Transport dimensions	1.390 mm × approx. 520 mm × 100 mm
Tray	Plastic
Tread depth	80 mm
Type rung/tread	serrated
Warranty	10 years
Weight	6 kg
Working height	2.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/28/2026

Subject to change or error.