

EFAmix S - 40431

The special ladders for all applications in electrical environments.

Product description

- The special ladders for all applications in electrical environments.
- Can be used for work on electrical installations, thanks to insulating stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478.
- Aluminium alloy treads, 80 mm deep, with non-slip serrated surface.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in an aluminium storage tray.
- Only 88 mm wide when folded.
- Treads made from extruded aluminium section.



Hints and special features

Complies with EN 131 Professional.

Product features

Base	Connection Stile-Rung	Load capacity	Material	Number of rungs, incl. platform
0,75 m × 0,52 m	flanged	max. 150 kg	Aluminium / plastic	3



ZARGES

Overall base width 0.52 m	Overall length 1.4 m	Pitch rung/tread 230 mm	Platform height 0.68 m	Platform length 250 mm
Platform width 250 mm	Standards EN 131 professional	Stile depth 50 mm	Stile depth 50 mm	Stile depth steps/back stay 50mm / 50mm
Transport dimensions 1.390 mm × approx. 520 mm × 100 mm	Tray Plastic	Tread depth 80 mm	Type rung/tread serrated	Warranty 10 years
Weight 6 kg	Working height 2.7 m			