

EFAmix S - 40431

The special ladders for all applications in electrical environments.

Product description

- The special ladders for all applications in electrical environments.
- Can be used for work on electrical installations, thanks to insulating stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478.
- Aluminium alloy treads, 80 mm deep, with non-slip serrated surface.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in an aluminium storage tray.
- Only 88 mm wide when folded.
- Treads made from extruded aluminium section.



Hints and special features

Complies with EN 131 Professional.

Product features

Base 0,75 m x 0,52 m	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium / plastic	Number of rungs, incl. platform 3



Overall base width	Overall length	Pitch rung/tread	Platform height	Platform length
0.52 m	1.4 m	230 mm	0.68 m	250 mm
Platform width	Standards	Stile depth	Stile depth	Stile depth steps/back stay
250 mm	EN 131 professional	50 mm	50 mm	50mm / 50mm
Transport dimensions	Tray	Tread depth	Type rung/tread	Warranty
1.390 mm x approx. 520 mm x 100 mm	Plastic	80 mm	serrated	10 years
Weight	Working height			
6 kg	2.7 m			