

# EFAmix S - 40435

The special ladders for all applications in electrical environments.

## Product description

- The special ladders for all applications in electrical environments.
- Can be used for work on electrical installations, thanks to insulating stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478.
- Aluminium alloy treads, 80 mm deep, with non-slip serrated surface.
- Safety platform (250 x 250 mm).
- Safe storage of accessories and tools in an aluminium storage tray.
- Only 88 mm wide when folded.
- Treads made from extruded aluminium section.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Base 1,4 m x 0,62 m	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium / plastic	Number of rungs, incl. platform 7



Overall base width	Overall length	Pitch rung/tread	Platform height	Platform length
<b>0.62 m</b>	<b>2.4 m</b>	<b>230 mm</b>	<b>1.6 m</b>	<b>250 mm</b>
Platform width	Standards	Stile depth	Stile depth	Stile depth steps/back stay
<b>250 mm</b>	<b>EN 131 professional</b>	<b>50 mm</b>	<b>50 mm</b>	<b>50mm / 50mm</b>
Transport dimensions	Tray	Tread depth	Type rung/tread	Warranty
<b>2.390 mm x approx. 620 mm x 100 mm</b>	<b>Plastic</b>	<b>80 mm</b>	<b>serrated</b>	<b>10 years</b>
Weight	Working height			
<b>10 kg</b>	<b>3.6 m</b>			