



Skyline 3E - 40447

When you need access to great heights: Optimised transport dimensions, working heights of up to 14.70 m with convenient height adjustment.

Product description

- When you need access to great heights: Optimised transport dimensions, working heights of up to 14.70 m with convenient height adjustment.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- Two ropes so that centre and top sections can be adjusted separately.
- Rung-by-rung height adjustment in a grid of 280 mm.
- The ladder with order no. 40448 is equipped with two lightweight metal supports for easy setup and stability. (Not for freestanding use!)
- Locks securely thanks to automatic spring loaded pawls.
- Improved plastic guide.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features



Certification	TÜV-SÜD
Coating	natural
Connection Stile-Rung	flanged
External width of lower ladder	560 mm
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	18
Number of rungs	3 × 18
Overall length, extended	12.55 m
Overall length, retracted	5.25 m
Pitch rung/tread	270 mm
Standards	EN 131 professional
Stile depth	86 mm
Stile depth	98 mm
Stile depth	86mm / 98mm
Transport dimensions	5.260 mm × 565 mm × 228 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	53 kg
Wheels	Rubber
Wide crosspiece	1.2 m



Working height

13.1 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/11/2026

Subject to change or error.