

Skyline 3E - 40448

When you need access to great heights: Optimised transport dimensions, working heights of up to 14.70 m with convenient height adjustment.

Product description

- When you need access to great heights: Optimised transport dimensions, working heights of up to 14.70 m with convenient height adjustment.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- Two ropes so that centre and top sections can be adjusted separately.
- Rung-by-rung height adjustment in a grid of 280 mm.
- The ladder with the Order No. 40448 is equipped with 2 light alloy supports for easy erection and stabilisation. (Not to be used as free-standing ladders!)
- Locks securely thanks to automatic spring loaded pawls.
- Improved plastic guide.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.



Product features

| | | | | |
|---|---|---|---|---|
| Coating natural | Connection Stile-Rung flanged | External width of lower ladder 590 mm | Load capacity max. 150 kg | Material Aluminium |
| Number of rungs 20 | Number of rungs 3 × 20 | Overall length, extended 14.2 m | Overall length, retracted 5.8 m | Pitch rung/tread 270 mm |
| Standards EN 131 professional | Stile depth 98 mm | Stile depth 98 mm | Stile depth 98mm / 98mm | Transport dimensions 5.820 mm × 718 mm × 242 mm |
| Tread depth 30 mm | Type rung/tread serrated | Warranty 10 years | Weight 68 kg | Wheels Rubber |
| Working height 14.7 m | certification-mark-pf TÜV-SÜD | | | |