

Skyline 3E - 40448

When you need access to great heights: Optimised transport dimensions, working heights of up to 14.70 m with convenient height adjustment.

Product description

- When you need access to great heights: Optimised transport dimensions, working heights of up to 14.70 m with convenient height adjustment.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- Two ropes so that centre and top sections can be adjusted separately.
- Rung-by-rung height adjustment in a grid of 280 mm.
- The ladder with the Order No. 40448 is equipped with 2 light alloy supports for easy erection and stabilisation. (Not to be used as free-standing ladders!)
- Locks securely thanks to automatic spring loaded pawls.
- Improved plastic guide.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 590 mm	Load capacity max. 150 kg	Material Aluminium
Number of rungs 20	Number of rungs 3 × 20	Overall length, extended 14.2 m	Overall length, retracted 5.8 m	Pitch rung/tread 270 mm
Standards EN 131 professional	Stile depth 98 mm	Stile depth 98 mm	Stile depth 98mm / 98mm	Transport dimensions 5.820 mm × 718 mm × 242 mm
Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years	Weight 68 kg	Wheels Rubber
Working height 14.7 m				