

# Seventec RC S - 40494

The ladder for optimal safety in outdoor areas.

## Product description

- The ladder for optimal safety in outdoor areas.
- Extra-deep treads with perforations for draining liquids (for use in oily or wet areas) and textured surface to ensure secure footing.
- Reflective strips on the stiles to improve visibility in poor visual conditions.
- 85 mm deep treads with perforation to allow liquids to flow off and profiling to ensure stability.
- Large safety platform (380 x 260 mm) with integrated hinged connection.
- Optimal stability thanks to the fold-down locking bar on both sides.
- Practical tray with plenty of space for tools and small items.
- Two integrated bucket hooks.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Smooth external stile surfaces that are comfortable to hold.
- Treads and stiles made from extruded aluminium sections.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti splay <b>Rigid locking bar</b>	Base <b>0,88 m × 0,48 m</b>	Coating <b>natural</b>	Connection Stile-Rung <b>riveted</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of rungs, incl. platform <b>4</b>	Overall base width <b>0.47 m</b>	Overall length <b>1.67 m</b>	Pitch rung/tread <b>218 mm</b>
Platform height <b>0.9 m</b>	Platform length <b>260 mm</b>	Platform width <b>380 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>87 mm</b>
Stile depth <b>87 mm</b>	Stile depth steps/back stay <b>87mm / 87mm</b>	Transport dimensions <b>1.680 mm × 490 mm × 250 mm</b>	Tray <b>Aluminium</b>	Tread depth <b>85 mm</b>
Type rung/tread <b>RC tread</b>	Vertical ladder height <b>1.54 m</b>	Warranty <b>10 years</b>	Weight <b>7.9 kg</b>	Working height <b>2.9 m</b>