


K 470 - Battery Case - 40582

For the safe storage and transport of defective or damaged lithium batteries in accordance with ADR P908 and SV 376.

Product description

- Maximum fire protection and easy handling thanks to the fireproof, one-piece interior construction, which also helps to avoid incorrect use.
- Hazardous goods packaging certified for lithium batteries UN 3480, UN 3481, UN 3090, UN 3091.
- Suitable for transporting prototypes, damaged or defective batteries, critically defective batteries and batteries for disposal and recycling.
- Fire test successfully passed. No inflammation. The neighbouring batteries remain intact. Temperatures on the outside of the box remain below 100°C.
- Padding and absorbent material are non-flammable, non-conductive and dust-free.
- Maximum outside temperature below 100°C, no flames or splinters escaping in the event of an accident.
- Capacity per compartment approx. 500 x 150 x 150 mm.
- High-quality special container made from aluminium.
- Equipped with fireproof padding and absorbent material made of textured glass fibres.



- Dust-free interior fittings.
- Tested and approved as hazardous goods packaging in accordance with UN requirements, i. e. can be transported on public roads.
- For storage and transport of defective or damaged lithium batteries in compliance with ADR special provisions 376 and packing instructions P908.
- New: Meets the specifications laid out by BAM in Special Provision SV 376 for the transport of critically defective lithium batteries.
- Follow the operating instructions.
- Made in Germany

Hints and special features

Approved hazardous goods packaging cannot be taken back.

Product features

Colour of the stacking corners Natural aluminium	Corner beading Yes	Fasteners Comfort fasteners	Handles Sprung drop handles	Integrated wheels No
Internal dimensions L x W x H 550 mm × 550 mm × 220 mm	Material Aluminium	Material of the stacking corners Aluminium	Max. gross weight dangerous goods permission 65 kg	Number of handles 2
Outside dimensions max. L x W x H 600 mm × 600 mm × 250 mm	Peripheral beading No	Seal foamed lid seal	Stacking corners Yes	Usable dimensions per compartment 500mm × 150mm × 180mm
Volume	Weight			



ZARGES

67 l

11.5 kg