

K 470 - Battery Case

Universal - 40583

Product description

- Maximum outside temperature below 100°C, no flames or splinters escaping in the event of an accident.
- Maximum fire protection and easy handling thanks to the fireproof, one-piece interior construction, which also helps to avoid incorrect use.
- Hazardous goods packaging certified for lithium batteries UN 3480, UN 3481, UN 3090, UN 3091.
- Suitable for transporting prototypes, damaged or defective batteries, critically defective batteries and batteries for disposal and recycling.
- High dielectric strength, i.e. also suitable for high-performance batteries, such as those used in power tools.
- Padding and absorbent material are non-flammable, non-conductive and dust-free.
- The box is also perfect for the storage of lithium-ion batteries.
- Increased thermal protection thanks to additional heat shields.



Hints and special features

Approved hazardous goods packaging cannot be taken back.

Usable dimensions approx. 415 x 215 x 95 mm.



Product features

Colour of the stacking corners Natural aluminium	Corner beading Yes	Fasteners Comfort fasteners	Handles Sprung drop handles	Integrated wheels No
Internal dimensions L x W x H 550 mm x 350 mm x 220 mm	Material Aluminium	Material of the stacking corners Aluminium	Max. gross weight dangerous goods permission 65 kg	Number of handles 3
Outside dimensions max. L x W x H 600 mm x 400 mm x 250 mm	Peripheral beading No	Seal foamed lid seal	Stacking corners Yes	Usable dimensions L x W x H 390mm x 190mm x 100mm
Volume 42 l	Weight 11.5 kg			