

W 170 trolley - 40635

The all-rounder: a sturdy box trolley for universal applications, for in-company logistics or for the transportation of waste.

Product description

- Robust and durable due to many quality features, e.g. sturdy, generously dimensioned edge and base profile, permanent connection to jacket and base plate using high-strength positive locking, riveted shell joint and welded frame profiles.
- High stiffness due to end and side walls reinforced with peripheral beading and corner beads.
- Effortless to manoeuvre due to easy-running, non-marking rubber wheels that are mounted on roller bearings and equipped with thread guards.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to jacket and base metal.
- End and side walls reinforced with peripheral beading and corner beads.
- Running gear: 2 swivel and 2 fixed castors, corner-mounted, Ø 125 mm, 40 mm wide, easy running, rubber wheels, "non-marking", roller bearings, thread guards.
- Casing joint riveted throughout. Frame profile sections welded.





Product features

Chassis arrangement can be changed Yes	Corner beading Yes	Formation Chassis 2 swivel and 2 fixed castors mounted at the corners	Internal dimensions L x W x H 1.250 mm × 700 mm × 750 mm	Material Aluminium
Outside dimensions max. L x W x H 1.300 mm × 750 mm × 955 mm	Peripheral beading Yes	Volume 655 l	Weight 23.7 kg	Wheel diameter 125 mm
Wheel diameter 40 mm				