


W 161 Spring Loaded Trolleys - 40756

No more bending over: easy access to items for ergonomic work. Ideal for laundries, goods logistics, libraries, or the food service industry.

Product description

- The base can move vertically to keep the contents at a constant height for easy access and work ergonomics.
- Interchangeable lifting elements for adjusting the strength, e.g., from 30 to 195 kg in 15-kg increments.
- No tilting, even with uneven loading.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to side walls and base.
- Beading for increased stability.
- Effortless to manoeuvre due to easy-running, non-marking rubber wheels that are mounted on roller bearings and equipped with thread guards.
- Castors arranged centrally for easy manoeuvring, even in the most confined spaces.
- A vertically adjustable floor that keeps the load at a consistent handling height.
- Anodised and featuring a reinforced edge profile for long-lasting durability.
- Chassis: 2 swivel casters and 2 fixed casters, 125 mm diameter, 40 mm width, smooth-rolling, rubber-wheeled, non-marking, ball-bearing mounted.
- Corner-mounted running gear available on request.





Product features

Chassis arrangement can be changed	Yes
Corner beading	Yes
Formation Chassis	2 swivel and 2 fixed castors in center arrangement
Internal dimensions L x W x H	1,410 mm × 700 mm × 580 mm
Material	Anodised aluminium
Outside dimensions max. L x W x H	1,460 mm × 750 mm × 920 mm
Spring force	150 kg
Volume	570 l
Weight	31.5 kg
Wheel diameter	125 mm
Wheel diameter	40 mm

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.