

EFAmix B - 41165

The ideal, particularly lightweight solution for work in electrical and chemical environments.

Product description

- The ideal, particularly lightweight solution for work in electrical and chemical environments.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Stand safely on 60 mm deep rungs made from non-slip aluminium alloy.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- High strength, non-twist rung/stile connections.
- Strong steel hinge.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	0,96 m × 0,48 m



Certification	TÜV-SÜD
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium / plastic
Number of rungs	4
Number of rungs	2 × 4
Overall base width	0.47 m
Overall length	1.34 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	1.344 mm × 480 mm × 162 mm
Tread depth	60 mm
Type rung/tread	serrated
Vertical ladder height	1.29 m
Warranty	10 years
Weight	7.8 kg
Working height	2.6 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.