

## EFAmix B - 41167

The ideal, particularly lightweight solution for work in electrical and chemical environments.

### Product description

- The ideal, particularly lightweight solution for work in electrical and chemical environments.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Stand safely on 60 mm deep rungs made from non-slip aluminium alloy.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- High strength, non-twist rung/stile connections.
- Strong steel hinge.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Anti splay	Belt strap
Base	1,31 m × 0,54 m



Certification	TÜV-SÜD
Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium / plastic
Number of rungs	6
Number of rungs	2 × 6
Overall base width	0.53 m
Overall length	1.9 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	1.904 mm × 540 mm × 162 mm
Tread depth	60 mm
Type rung/tread	serrated
Vertical ladder height	1.82 m
Warranty	10 years
Weight	11.4 kg
Working height	3.1 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 5/13/2026

Subject to change or error.