

EFAmix B - 41168

The ideal, particularly lightweight solution for work in electrical and chemical environments.

Product description

- The ideal, particularly lightweight solution for work in electrical and chemical environments.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Stand safely on 60 mm deep rungs made from non-slip aluminium alloy.
- High-strength perlon belts prevent splay.
- High strength, non-twist rung/stile connections.
- Strong steel hinge.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Base 1,81 m × 0,6 m	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium / plastic
---------------------------------	-------------------------------	---	-------------------------------------	--

Number of rungs 8	Number of rungs 2 × 8	Overall base width 0.59 m	Overall length 2.46 m	Pitch rung/tread 265 mm
Standards EN 131 professional	Stile depth 58 mm	Transport dimensions 2.464 mm × 600 mm × 162 mm	Tread depth 60 mm	Type rung/tread serrated
Vertical ladder height 2.33 m	Warranty 10 years	Weight 14.8 kg	Working height 3.65 m	