

EFAmix B - 41169

The ideal, particularly lightweight solution for work in electrical and chemical environments.

Product description

- The ideal, particularly lightweight solution for work in electrical and chemical environments.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Stand safely on 60 mm deep rungs made from non-slip aluminium alloy.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- High strength, non-twist rung/stile connections.
- Strong steel hinge.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|------------|-----------------|
| Anti splay | Belt strap |
| Base | 2,17 m × 0,66 m |



| | |
|------------------------|----------------------------|
| Certification | TÜV-SÜD |
| Connection Stile-Rung | flanged |
| Load capacity | max. 150 kg |
| Material | Aluminium / plastic |
| Number of rungs | 10 |
| Number of rungs | 2 × 10 |
| Overall base width | 0.65 m |
| Overall length | 3.02 m |
| Pitch rung/tread | 265 mm |
| Standards | EN 131 professional |
| Stile depth | 58 mm |
| Transport dimensions | 3.024 mm × 660 mm × 162 mm |
| Tread depth | 60 mm |
| Type rung/tread | serrated |
| Vertical ladder height | 2.86 m |
| Warranty | 10 years |
| Weight | 18.8 kg |
| Working height | 4.15 m |

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/13/2026

Subject to change or error.