

## EFAmix B - 41170

The ideal, particularly lightweight solution for work in electrical and chemical environments.

### Product description

- The ideal, particularly lightweight solution for work in electrical and chemical environments.
- High level of protection provided for working on electrical installations thanks to insulated stiles made from glass-fibre-reinforced plastic.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Stand safely on 60 mm deep rungs made from non-slip aluminium alloy.
- High-strength perlon belts prevent splay.
- High strength, non-twist rung/stile connections.
- Strong steel hinge.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Anti splay <b>Belt strap</b>	Base <b>2,55 m × 0,72 m</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium / plastic</b>
---------------------------------	--------------------------------	---	-------------------------------------	--

Number of rungs <b>12</b>	Number of rungs <b>2 × 12</b>	Overall base width <b>0.71 m</b>	Overall length <b>3.58 m</b>	Pitch rung/tread <b>265 mm</b>
Standards <b>EN 131 professional</b>	Stile depth <b>58 mm</b>	Transport dimensions <b>3.584 mm × 720 mm × 162 mm</b>	Tread depth <b>60 mm</b>	Type rung/tread <b>serrated</b>
Vertical ladder height <b>3.38 m</b>	Warranty <b>10 years</b>	Weight <b>22.5 kg</b>	Working height <b>4.7 m</b>	