

Megastep B - 41190

Extreme strength in a double-sided version: 250 kg load capacity, combined with relatively low weight, for the most demanding applications.

Product description

- Extreme strength in a double-sided version: 250 kg load capacity, combined with relatively low weight, for the most demanding applications.
- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Clean hands thanks to wear-resistant, anodised black styles.
- Strong steel hinges.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Sturdy design: flanged rungs-to-stiles connection with extruded aluminum profiles.



Hints and special features

Complies with EN 131 Professional.

Product features

| | |
|------------|---------------|
| Anti splay | Belt strap |
| Base | 1,1 m × 0,5 m |



| | |
|------------------------|----------------------------|
| Certification | TÜV-SÜD |
| Coating | anodised |
| Connection Stile-Rung | flanged |
| Load capacity | max. 250 kg |
| Material | Aluminium |
| Number of rungs | 5 |
| Number of rungs | 2 × 5 |
| Overall base width | 0.5 m |
| Overall length | 1.5 m |
| Pitch rung/tread | 265 mm |
| Standards | EN 131 professional |
| Stile depth | 73 mm |
| Transport dimensions | 1,535 mm × 510 mm × 190 mm |
| Tread depth | 60 mm |
| Type rung/tread | SL Step |
| Vertical ladder height | 1.47 m |
| Warranty | 10 years |
| Weight | 8 kg |
| Working height | 2.75 m |

ZARGES GmbH

Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 5/12/2026

Subject to change or error.