

# Megastep B - 41190

Design from both sides: high load capacity with flexible application options and an exclusive design with luxurious black finish.

## Product description

- Design from both sides: high load capacity with flexible application options and an exclusive design with luxurious black finish.
- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Black, wear-resistant anodised stiles.
- Strong steel hinges.
- High-strength perlon belts prevent splay.
- Rungs and stiles made from extruded aluminium sections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
<b>Belt strap</b>	<b>1,1 m × 0,5 m</b>	<b>anodised</b>	<b>flanged</b>	<b>max. 250 kg</b>
Material	Number of rungs	Number of rungs	Overall base width	Overall length

<b>Aluminium</b>	<b>5</b>	<b>2 × 5</b>	<b>0.5 m</b>	<b>1.5 m</b>
Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>73 mm</b>	Transport dimensions <b>1.535 mm × 510 mm × 190 mm</b>	Tread depth <b>60 mm</b>
Type rung/tread <b>SL Step</b>	Vertical ladder height <b>1.47 m</b>	Warranty <b>10 years</b>	Weight <b>8 kg</b>	Working height <b>2.75 m</b>
certification-mark-pf <b>TÜV-SÜD</b>				