

Megastep B - 41191

Extreme strength in a double-sided version: 250 kg load capacity, combined with relatively low weight, for the most demanding applications.

Product description

- Extreme strength in a double-sided version: 250 kg load capacity, combined with relatively low weight, for the most demanding applications.
- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Clean hands thanks to wear-resistant, anodised black styles.
- Strong steel hinges.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Sturdy design: flanged rungs-to-stiles connection with extruded aluminum profiles.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	1,28 m × 0,53 m



Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	flanged
Load capacity	max. 250 kg
Material	Aluminium
Number of rungs	6
Number of rungs	2 × 6
Overall base width	0.53 m
Overall length	1.78 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	73 mm
Transport dimensions	1.815 mm × 540 mm × 190 mm
Tread depth	60 mm
Type rung/tread	SL Step
Vertical ladder height	1.73 m
Warranty	10 years
Weight	8.9 kg
Working height	3 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/26/2026

Subject to change or error.