

Megastep B - 41191

Design from both sides: high load capacity with flexible application options and an exclusive design with luxurious black finish.

Product description

- Design from both sides: high load capacity with flexible application options and an exclusive design with luxurious black finish.
- Max. load 250 kg.
- Wide aluminium alloy rungs, 60 mm deep, with non-slip ribbing.
- Black, wear-resistant anodised stiles.
- Strong steel hinges.
- High-strength perlon belts prevent splay.
- Rungs and stiles made from extruded aluminium sections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|-------------------|------------------------|-----------------|-----------------------|--------------------|
| Anti splay | Base | Coating | Connection Stile-Rung | Load capacity |
| Belt strap | 1,28 m x 0,53 m | anodised | flanged | max. 250 kg |
| Material | Number of rungs | Number of rungs | Overall base width | Overall length |



| | | | | |
|-----------------------------------|---|-----------------------------|---|------------------------------|
| Aluminium | 6 | 2 × 6 | 0.53 m | 1.78 m |
| Pitch rung/tread 265 mm | Standards EN 131 professional | Stile depth 73 mm | Transport dimensions 1.815 mm × 540 mm × 190 mm | Tread depth 60 mm |
| Type rung/tread SL Step | Vertical ladder height 1.73 m | Warranty 10 years | Weight 8.9 kg | Working height 3 m |
| certification-mark-pf | | | | TÜV-SÜD |