

XLstep S - 41224

Low weight, simple handling and a good price/performance ratio with high-value equipment.

Product description

- Low weight, simple handling and a good price/performance ratio with high-value equipment.
- Stand without fatigue on deep treads.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm x 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength perlon belts prevent splay.
- Triple-riveted connection between treads and stiles.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features



Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
Belt strap	0,91 m × 0,52 m	anodised	riveted	max. 150 kg
Material	Number of rungs, incl. platform	Overall base width	Overall length	Pitch rung/tread
Aluminium	4	0.52 m	1.83 m	250 mm
Platform height	Platform length	Platform width	Standards	Stile depth
0.99 m	250 mm	300 mm	EN 131 professional	42 mm
Stile depth	Stile depth steps/back stay	Transport dimensions	Tray	Tread depth
42 mm	42mm / 42mm	approx. 1.830 mm × approx. 520 mm × approx. 155 mm	Aluminium	80 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
serrated	1.67 m	10 years	6.9 kg	3 m
certification-mark-pf				
TÜV-SÜD				