



XLstep S - 41225

Designed for frequent relocation: lightweight and durable, with a wide platform, a storage tray, and sturdy ladder end caps.

Product description

- Designed for frequent relocation: lightweight and durable, with a wide platform, a storage tray, and sturdy ladder end caps.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Non-slip two-component ladder feet with a large contact surface.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Clean hands thanks to wear-resistant anodised stiles.
- Spacious aluminum storage tray with plenty of room for tools and small parts.
- Easy access up and down via sturdy 80-mm-deep treads.
- Triple-riveted connection between treads and stiles.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Sturdy design for daily use: platform and profiles made of extruded aluminum.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	1,08 m × 0,56 m
Certification	TÜV-SÜD
Coating	anodised
Connection Stile-Rung	riveted
Load capacity	max. 150 kg
Material	Aluminium
Number of rungs, incl. platform	5
Overall base width	0.56 m
Overall length	2.1 m
Pitch rung/tread	250 mm
Platform height	1.24 m
Platform length	250 mm
Platform width	300 mm
Standards	EN 131 professional
Stile depth	42 mm
Stile depth	42 mm
Stile depth steps/back stay	42mm / 42mm
Transport dimensions	approx. 2.100 mm × approx. 560 mm × approx. 155 mm
Tray	Aluminium



Tread depth	80 mm
Type rung/tread	serrated
Vertical ladder height	1.92 m
Warranty	10 years
Weight	7.7 kg
Working height	3.25 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 7/1/2026

Subject to change or error.