

## XLstep S - 41228

Low weight, simple handling and a good price/performance ratio with high-value equipment.

### Product description

- Low weight, simple handling and a good price/performance ratio with high-value equipment.
- Stand without fatigue on deep treads.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm x 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength perlon belts prevent splay.
- Triple-riveted connection between treads and stiles.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.



### Hints and special features

Complies with EN 131 Professional.

### Product features



Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
<b>Belt strap</b>	<b>1,59 m x 0,63 m</b>	<b>anodised</b>	<b>riveted</b>	<b>max. 150 kg</b>
Material	Number of rungs, incl. platform	Overall base width	Overall length	Pitch rung/tread
<b>Aluminium</b>	<b>8</b>	<b>0.63 m</b>	<b>2.91 m</b>	<b>250 mm</b>
Platform height	Platform length	Platform width	Standards	Stile depth
<b>1.99 m</b>	<b>250 mm</b>	<b>300 mm</b>	<b>EN 131 professional</b>	<b>48 mm</b>
Stile depth	Stile depth steps/back stay	Transport dimensions	Tray	Tread depth
<b>42 mm</b>	<b>48mm / 42mm</b>	<b>approx. 2.910 mm x approx. 630 mm x approx. 155 mm</b>	<b>Aluminium</b>	<b>80 mm</b>
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
<b>serrated</b>	<b>2.67 m</b>	<b>10 years</b>	<b>11.7 kg</b>	<b>4 m</b>
certification-mark-pf <b>TÜV-SÜD</b>				