

## XLstep S - 41228

Low weight, simple handling and a good price/performance ratio with high-value equipment.

### Product description

- Low weight, simple handling and a good price/performance ratio with high-value equipment.
- Stand without fatigue on deep treads.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength perlon belts prevent splay.
- Triple-riveted connection between treads and stiles.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Anti splay <b>Belt strap</b>	Base <b>1,59 m × 0,63 m</b>	Coating <b>anodised</b>	Connection Stile-Rung <b>riveted</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of rungs, incl. platform <b>8</b>	Overall base width <b>0.63 m</b>	Overall length <b>2.91 m</b>	Pitch rung/tread <b>250 mm</b>
Platform height <b>1.99 m</b>	Platform length <b>250 mm</b>	Platform width <b>300 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>48 mm</b>
Stile depth <b>42 mm</b>	Stile depth steps/back stay <b>48mm / 42mm</b>	Transport dimensions <b>approx. 2.910 mm × approx. 630 mm × approx. 155 mm</b>	Tray <b>Aluminium</b>	Tread depth <b>80 mm</b>
Type rung/tread <b>serrated</b>	Vertical ladder height <b>2.67 m</b>	Warranty <b>10 years</b>	Weight <b>11.7 kg</b>	Working height <b>4 m</b>
certification-mark-pf <b>TÜV-SÜD</b>				