

XLstep S - 41230

Low weight, simple handling and a good price/performance ratio with high-value equipment.

Product description

- Low weight, simple handling and a good price/performance ratio with high-value equipment.
- Stand without fatigue on deep treads.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Spacious aluminium storage tray for material and tools.
- High-strength perlon belts prevent splay.
- Triple-riveted connection between treads and stiles.
- Non-slip plastic end caps.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Base 1,93 m × 0,69 m	Coating anodised	Connection Stile-Rung riveted	Load capacity max. 150 kg
Material Aluminium	Number of rungs, incl. platform 10	Overall base width 0.69 m	Overall length 3.45 m	Pitch rung/tread 250 mm
Platform height 2.49 m	Platform length 250 mm	Platform width 300 mm	Standards EN 131 professional	Stile depth 48 mm
Stile depth 42 mm	Stile depth steps/back stay 48mm / 42mm	Transport dimensions approx. 3.450 mm × approx. 690 mm × approx. 155 mm	Tray Aluminium	Tread depth 80 mm
Type rung/tread serrated	Vertical ladder height 3.17 m	Warranty 10 years	Weight 14.1 kg	Working height 4.5 m
certification-mark-pf TÜV-SÜD				