

Roof ladders - 41235

Safe access to various roof pitches via high-stability stationary ladder with rungs arranged eccentrically.

Product description

- Safe access to various roof pitches via high-stability stationary ladder with rungs arranged eccentrically.
- Safe, square rungs with 2 differently inclined tread surfaces.
- Robust stile sections ensure 80 mm safety clearance between the rungs and the roof surface.
- Problem-free coordination of the ladder to the relevant roof length.
- Off-centre rung arrangement.
- Maximum loading capacity 150 kg.
- Outside width: 340 mm.
- High strength, non-twist rung/stile connections.
- Rungs made from extruded aluminium sections for maximum safety.



Hints and special features

Connecting straps are included with every roof ladder as standard.

Product features

Coating	powder-coated
Colour	Brick-red
Connection Stile-Rung	flanged
Ladder width	340 mm



Load capacity	max. 150 kg
Material	Aluminium
Number of rungs	15
Overall length	4.2 m
Pitch rung/tread	280 mm
Stile depth	110 mm
Transport dimensions	4.200 mm × 340 mm × 110 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	6.8 kg

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/28/2026

Subject to change or error.