



## EFA L - 41251

The safety ladder for quick application in chemical or electrical environments.

### Product description

- The safety ladder for quick application in chemical or electrical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Outside width: 420 mm - particularly stable.



### Hints and special features

in accordance with DIN EN 131-1, order No. 41255

includes a stabiliser bar.

Complies with EN 131 Professional.

### Product features

Load capacity	Material	Number of rungs	Overall length	Pitch rung/tread
---------------	----------	-----------------	----------------	------------------



max. 150 kg	Glass-fibre reinforced plastic	6	1.92 m	265 mm
Standards <b>EN 131 professional</b>	Stile depth <b>58 mm</b>	Transport dimensions <b>1.924 mm × 430 mm × 70 mm</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>
Warranty <b>10 years</b>	Weight <b>5.6 kg</b>	Working height <b>2.8 m</b>	certification-mark-pf <b>TÜV-SÜD</b>	