



## EFA L - 41253

The safety ladder for quick application in chemical or electrical environments.

### Product description

- The safety ladder for quick application in chemical or electrical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Outside width: 420 mm - particularly stable.



### Hints and special features

in accordance with DIN EN 131-1, order No. 41255

includes a stabiliser bar.

Complies with EN 131 Professional.

### Product features

Certification	TÜV-SÜD
Load capacity	max. 150 kg



Material	Glass-fibre reinforced plastic
Number of rungs	10
Overall length	2.993 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	3.044 mm × 430 mm × 70 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	8.6 kg
Working height	3.85 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 5/21/2026

Subject to change or error.