

EFA L - 41255

The safety ladder for quick application in chemical or electrical environments.

Product description

- The safety ladder for quick application in chemical or electrical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Outside width: 420 mm - particularly stable.



Hints and special features

in accordance with DIN EN 131-1, order No. 41255

includes a stabiliser bar.

Complies with EN 131 Professional.

Product features

Load capacity	Material	Number of rungs	Overall length	Pitch rung/tread
---------------	----------	-----------------	----------------	------------------



max. 150 kg	Glass-fibre reinforced plastic	14	4.16 m	265 mm
Standards EN 131 professional	Stile depth 73 mm	Transport dimensions 4.164 mm × 430 mm × 70 mm	Tread depth 30 mm	Type rung/tread serrated
Warranty 10 years	Weight 12.4 kg	Wide crosspiece 0.9 m	Working height 4.95 m	