

## EFA B - 41256

For flexible applications in electrical or chemical environments and for working under voltage.

### Product description


- For flexible applications in electrical or chemical environments and for working under voltage.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Complies with EN 131 Professional.

### Product features



Anti splay <b>Belt strap</b>	Base <b>1,31 m × 0,54 m</b>	Load capacity <b>max. 150 kg</b>	Material <b>Glass-fibre reinforced plastic</b>	Number of rungs <b>6</b>
Number of rungs <b>2 × 6</b>	Overall base width <b>0.54 m</b>	Overall length <b>1.88 m</b>	Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>
Stile depth <b>58 mm</b>	Transport dimensions <b>1.900 mm × 540 mm × 162 mm</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>	Vertical ladder height <b>1.82 m</b>
Warranty <b>10 years</b>	Weight <b>10.5 kg</b>	Working height <b>3.1 m</b>		