
DATA SHEET

EFA B - 41261

For flexible applications in electrical or chemical environments and for working under voltage.







PRODUCT DESCRIPTION

- For flexible applications in electrical or chemical environments and for working under voltage.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Stiles and rungs (30 x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Replaceable 2-component plastic end caps ensure positioning without the risk of slipping and at the same time provide firm seating in the stile.

HINTS AND SPECIAL FEATURES

Complies with EN 131 Professional.

PRODUCT FEATURES

Property	Value
Anti splay	Belt strap

Property	Value
Base	1,08 m × 0,48 m
Certification	TÜV-SÜD
Load capacity	max. 150 kg
Material	Glass-fibre reinforced plastic
Number of rungs	4
Number of rungs	2 × 4
Overall base width	0.48 m
Overall length	1.32 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	58 mm
Transport dimensions	1.350 mm × 480 mm × 162 mm
Tread depth	30 mm
Type rung/tread	serrated
Vertical ladder height	1.27 m
Warranty	10 years
Weight	7.5 kg
Working height	2.6 m

ACCESSORIES AND SPARE PARTS

ACCESSORIES 5



Ground spikes
SKU 40939



Hook-on platform
SKU 40450



Hook-on tool box
SKU 40920



Ladder holder, lockable
SKU 40998



Tension strap
SKU 40960

SPARE PARTS 7



Bushing
SKU 824456



End cap
SKU 824152



Hinge
SKU 820418



Push-on end cap
SKU 824409



Splay prevention (belt strap)
SKU 829669



Stop bracket
SKU 809499



User instructions label
SKU 800606

ZARGES GMBH
Zargesstraße 7
82362 Weilheim

Tel: +49 (0)881-687-100
Fax: +49 (0)881-687-500
zarges@zarges.de

www.zarges.com
Effective 11/10/2026
Subject to change or error.