

XLstep B - 41265

Low weight and optimum price/performance ratio without compromising on comfort or equipment.

Product description

- Low weight and optimum price/performance ratio without compromising on comfort or equipment.
- Stand without fatigue on deep treads.
- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- Triple-riveted connection between treads and stiles.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
Belt strap	1,12 m x 0,5 m	anodised	riveted	max. 150 kg
Material	Number of treads	Number of treads	Overall base width	Overall length
Aluminium	5	2 x 5	0.5 m	1.36 m
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth
250 mm	EN 131 professional	42 mm	1.360 mm x 500 mm x 170 mm	80 mm



ZARGES

Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
serrated	1.24 m	10 years	4.5 kg	2.75 m
certification-mark-pf				
TÜV-SÜD				

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

www.zarges.com

zarges@zarges.de

Effective
2/12/2026

Subject to change or error.

2/2