

XLstep B - 41265

Low weight and optimum price/performance ratio without compromising on comfort or equipment.

Product description

- Low weight and optimum price/performance ratio without compromising on comfort or equipment.
- Stand without fatigue on deep treads.
- Treads with a depth of 80 mm for fatigue-free standing.
- Abrasion-resistant, anodised stiles.
- High-strength perlon belts prevent splay.
- Triple-riveted connection between treads and stiles.
- Treads and stiles made from extruded aluminium sections.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay	Belt strap
Base	1,12 m × 0,5 m
Coating	anodised
Connection Stile-Rung	riveted
Load capacity	max. 150 kg
Material	Aluminium
Number of treads	5



Number of treads	2 × 5
Overall base width	0.5 m
Overall length	1.36 m
Pitch rung/tread	250 mm
Standards	EN 131 professional
Stile depth	42 mm
Transport dimensions	1.360 mm × 500 mm × 170 mm
Tread depth	80 mm
Type rung/tread	serrated
Vertical ladder height	1.24 m
Warranty	10 years
Weight	4.5 kg
Working height	2.75 m
certification-mark-pf	TÜV-SÜD

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 3/29/2026

Subject to change or error.