

# XLstep B - 41266

Accessible from both sides, easy to carry, durable in use: perfect for frequent moves.

## Product description

- Accessible from both sides, easy to carry, durable in use: perfect for frequent moves.
- Easy access up and down via sturdy 80-mm-deep treads.
- Non-slip two-component ladder feet with a large contact surface.
- Clean hands thanks to wear-resistant anodised stiles.
- Triple-riveted connection between treads and stiles.
- High-strength polyester webbing with a sewn-in attachment loop – durable and resistant to wear and tear.
- Durable design for everyday use: extruded aluminum profiles.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti splay	Belt strap
Base	1,34 m × 0,54 m
Certification	TÜV-SÜD
Coating	anodised



Connection Stile-Rung	riveted
Load capacity	max. 150 kg
Material	Aluminium
Number of treads	6
Number of treads	2 × 6
Overall base width	0.54 m
Overall length	1.63 m
Pitch rung/tread	250 mm
Standards	EN 131 professional
Stile depth	42 mm
Transport dimensions	1.630 mm × 530 mm × 170 mm
Tread depth	80 mm
Type rung/tread	serrated
Vertical ladder height	1.49 m
Warranty	10 years
Weight	6.9 kg
Working height	3 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 7/2/2026

Subject to change or error.