



Skyline EFA 2E - 41274

For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.

Product description

- For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Wall wheels that will not damage the wall.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.



Product features

External width of lower ladder	420 mm
Load capacity	max. 150 kg
Material	Glass-fibre reinforced plastic
Number of rungs	14
Number of rungs	2 × 14
Overall length, extended	7.17 m
Overall length, retracted	4.09 m
Pitch rung/tread	270 mm
Standards	EN 131 professional
Stile depth	90 mm
Transport dimensions	4.100 mm × 470 mm × 150 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	35.7 kg
Wheels	Rubber
Wide crosspiece	1.1 m
Working height	7.95 m
certification-mark-pf	TÜV-SÜD



ZARGES

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 3/27/2026

Subject to change or error.