

## Skyline EFA 2E - 41274

For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.

### Product description

- For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Wall wheels that will not damage the wall.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.





## Hints and special features

Complies with EN 131 Professional.

## Product features

External width of lower ladder <b>420 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>Glass-fibre reinforced plastic</b>	Number of rungs <b>14</b>	Number of rungs <b>2 × 14</b>
Overall length, extended <b>7.17 m</b>	Overall length, retracted <b>4.09 m</b>	Pitch rung/tread <b>270 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>90 mm</b>
Transport dimensions <b>4.100 mm × 470 mm × 150 mm</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>	Weight <b>35.7 kg</b>
Wheels <b>Rubber</b>	Wide crosspiece <b>1.1 m</b>	Working height <b>7.95 m</b>	certification-mark-pf <b>TÜV-SÜD</b>	