

Everest EFA 2E - 41290

Plastic ladder for access to great heights, for use in electrical and chemical environments.

Product description

- Plastic ladder for access to great heights, for use in electrical and chemical environments.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 41288-41290.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Both parts of the ladder can also be used separately as single ladders.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- External width of lower ladder: 420 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.



Product features

Certification	TÜV-SÜD
External width of lower ladder	420 mm
Load capacity	max. 150 kg
Material	Glass-fibre reinforced plastic
Number of rungs	10
Number of rungs	2 × 10
Overall length, extended	4.91 m
Overall length, retracted	2.95 m
Pitch rung/tread	270 mm
Standards	EN 131 professional
Stile depth	73 mm
Transport dimensions	2.950 mm × 430 mm × 150 mm
Tread depth	30 mm
Type rung/tread	serrated
Warranty	10 years
Weight	19.5 kg
Wide crosspiece	0.9 m
Working height	5.7 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

www.zarges.com

Effective 6/28/2026

Subject to change or error.