

Saferstep B - 41303

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- · Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Maximum working heights thanks to 280mm high access.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Base 0,8 m × 0,44 m	Coating anodised	Connection Stile-Rung flanged	Load capacity max. 150 kg
Material Aluminium	Number of treads	Number of treads 2 × 3	Overall base width 0.44 m	Overall length 0.88 m

ZARGES GmbH Zargesstraße 7 Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 www.zarges.com zarges@zarges.de



Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth
265 mm	EN 131 professional	68 mm	875 mm × 445 mm × 230 mm	80 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
Safer Step	0.8 m	10 years	4.6 kg	2.3 m

82362 Weilheim