

# Saferstep B - 41303

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.



## Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Maximum working heights thanks to 280mm high access.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
<b>Belt strap</b>	<b>0,8 m x 0,44 m</b>	<b>anodised</b>	<b>flanged</b>	<b>max. 150 kg</b>
Material	Number of treads	Number of treads	Overall base width	Overall length
<b>Aluminium</b>	<b>3</b>	<b>2 x 3</b>	<b>0,44 m</b>	<b>0,88 m</b>



Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>68 mm</b>	Transport dimensions <b>875 mm × 445 mm × 230 mm</b>	Tread depth <b>80 mm</b>
Type rung/tread <b>Safer Step</b>	Vertical ladder height <b>0.8 m</b>	Warranty <b>10 years</b>	Weight <b>4.6 kg</b>	Working height <b>2.3 m</b>
certification-mark-pf				<b>TÜV-SÜD</b>