

# Saferstep B - 41303

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

## Product description

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Anti splay	Belt strap
Base	0,8 m × 0,44 m
Certification	TÜV-SÜD
Coating	anodised



Connection Stile-Rung	flanged
Load capacity	max. 150 kg
Material	Aluminium
Number of treads	3
Number of treads	2 × 3
Overall base width	0.44 m
Overall length	0.88 m
Pitch rung/tread	265 mm
Standards	EN 131 professional
Stile depth	68 mm
Transport dimensions	approx. 880 mm × 445 mm × approx. 215 mm
Tread depth	80 mm
Type rung/tread	Safer Step
Vertical ladder height	0.8 m
Warranty	10 years
Weight	4.6 kg
Working height	2.3 m

ZARGES GmbH

Zargesstraße 7

82362 Weilheim

Tel: +49 (0)881-687-100

Fax: +49 (0)881-687-500

zarges@zarges.de

[www.zarges.com](http://www.zarges.com)

Effective 4/7/2026

Subject to change or error.