

# Saferstep B - 41304

The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.

### **Product description**

- The comfort version for flexible application, with high safety due to the use of Safer Step Technology and pleasant to grip.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- · Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.
- Maximum working heights thanks to 280mm high access.



## Hints and special features

Complies with EN 131 Professional.

### **Product features**

Anti splay  Belt strap	Base <b>0,99 m × 0,47 m</b>	Coating anodised	Connection Stile-Rung flanged	Load capacity max. 150 kg
Material <b>Aluminium</b>	Number of treads	Number of treads 2 × 4	Overall base width  0.47 m	Overall length

ZARGES GmbH Zargesstraße 7 Tel: +49 (0)881-687-100 Fax: +49 (0)881-687-500 www.zarges.com zarges@zarges.de

Effective 12/5/2025



Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth
265 mm	EN 131 professional	68 mm	1.153 mm × 475 mm × 230 mm	80 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
Safer Step	1.06 m	10 years	6.1 kg	2.55 m

82362 Weilheim